



Tadiran T31G

User Friendly, Entry Level IP Phone

Tadiran's T31G is an easy to use, feature rich Gigabit IP phone with superior audio for excellent communications.

Highlights:

- 2.3", 132x64 pixel graphical LCD with backlight
- Dual port Gigabit Ethernet
- Wall mountable
- PoE Support
- Support of Aeonix automatic provisioning mechanism
- Multi Language Support
- Extended SIP Functionality (ESF) provided by Aeonix

Features:

- Call hold, mute, DND
- One-touch speed dial, hotline
- Redial, call return, auto answer
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Local 5-way conferencing
- Ringtone selection/import/delete
- Keypad lock, emergency call
- Set date time manually or automatically
- Dial Plan, XML Browser, action URL & action URI
- Integrated Screenshots
- RTCP-XR, VQ-RTCPXR

Codecs and Voice Features:

- Narrowband Codec: G.711(A/μ), G.723, G.729A, G.726, iLBC
- Wideband Codec: Opus, G.722
- VAD, CNG, AEC, PLC, AJB, AGC

Management:

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deployment
- Auto-provision with PnP
- Reset to factory, reboot
- Package tracing export, system log
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection

Additional Features:

- Busy Lamp Field (BLF)
- Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Message Waiting Indicator (MWI)
- Call park, call pickup
- Intercom, paging, music on hold, emergency call
- Paper label-free design
- Stand with two adjustable angles

Network and Security Features:

- SIP v1 (RFC2543), v2 (RFC3261)
- IPv6
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- IEEE802.1X



Physical Features:

- Dual port Gigabit Ethernet
- 2 line keys with LED
- 6 feature keys: transfer, message, headset, redial, mute, hands-free speakerphone
- 5 navigation keys
- 2 Volume control keys
- Paperless label design
- 1 x RJ9 handset port, 1 x RJ9 headset port
- Wall mountable (optional)
- Power adapter (optional): AC 100~240V input and DC 5V/600mA output
- Power over Ethernet (IEEE 802.3af), Class 2
- Power consumption (PSU): 2-3W
- Dimensions (W*D*H*T): 188mm*189mm*162mm*50mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C



About Tadiran:

Tadiran Telecom (TTL) L.P. is a privately held partnership, owned by Afcon Holdings Ltd. and part of the Shlomo Group. It is an established global provider of Unified Communications & Collaboration (UC&C), Contact Center, and Control Room solutions, serving businesses of all sizes, including tier-1 organizations in various market segments in 41 countries worldwide. Tadiran solutions feature a comprehensive family of products including UC platforms, UCaaS, Contact Centers, Dispatch Console, IP phones and mobility and desktop solutions.

Visit us at: www.tadirantele.com

Copyright © 2021 Tadiran Telecom (TTL) L.P. Specifications subject to change without notice. All other products or services mentioned are the trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Israel +972-3-9262000
USA +1-678-506-7200

China +86-10-58696418
India +91-11-41523168/23353822