



Tadiran T46U

A Revolutionary SIP Phone for Enhancing Productivity

Tadiran's T46U is designed for busy executives and professionals. The T46U phone is an ultimate communication tool that has excellent price / performance. The phone employs an appealing high-resolution TFT color display that is bright and vibrant.

Highlights:

- 4.3" 480 x 272-pixel color display with backlight
- Opus codec support
- Dual USB ports
- Dual-port Gigabit Ethernet
- PoE support
- USB headset and EHS support
- Wi-Fi via WF40/WF50
- Bluetooth via BT40/BT41
- Supports color-screen expansion modules
- Stand with two adjustable angles
- Wall mountable

Features:

- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Redial, call return, auto answer
- Ring tone selection/import/delete
- Set date time manually or automatically
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Enhanced DSS Key
- Wi-Fi through WF40/WF50

Management:

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

Additional Features:

- 6 features keys: transfer, message, headset, redial, mute, hands-free speakerphone
- 5 navigation keys
- Volume control keys
- Busy Lamp Field (BLF)
- Bridged Line Appearance (BLA)



Network and Security Protocols:

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication
- OpenVPN, IEEE802.1X
- LLDP/CDP/DHCP VLAN, ICE

Physical Features:

- 4.3" 480 x 272-pixel color display with backlight
- Color: Classic Grey
- Stand with 2 adjustable angles
- Wall mountable
- External Yealink AC adapter (optional): AC 100~240V input and DC 5V/600mA output
- USB output currency: 5V 1A
- Power consumption (PSU): 1.2-3.0W
- Power consumption (PoE): 1.6-3.8W
- Dimension (W*D*H*T): 244mm*213mm*185mm*54mm
- Operating humidity: 10~95%
- Operating temperature: 0~40°C (+32~104°F)

About Tadiran:

Tadiran Telecom (TTL) L.P. is a privately held partnership, owned by Afcon Holdings Ltd. and part of the Shlomo Group. It is an established global provider of Unified Communications & Collaboration (UC&C), Contact Center, and Control Room solutions, serving businesses of all sizes, including tier-1 organizations in various market segments in 41 countries worldwide. Tadiran solutions feature a comprehensive family of products including UC platforms, UCaaS, Contact Centers, Dispatch Console, IP phones and mobility and desktop solutions.

Visit us at: www.tadirantele.com

Copyright © 2022 Tadiran Telecom (TTL) L.P. Specifications subject to change without notice. All other products or services mentioned are the trademarks, service marks, registered trademarks or registered service marks of their respective owners.